



## NEO Series

### Description:

Neo System Case was featured with Fan-Less CPU Cooling, Simple, Compact, Small, Stylish. It can be applied as Thin Client, NetWork Device, Set-Top Box, VPN, VOIP and POS system. Major Material is Aluminum for good heat solution, For VIA C3 800Mhz - 1Ghz CPU System, NEO System can operate very well with out CPU Cooler Fan and it can reduce the possibility of Fan System Fail Situation. NEO System Case provides 1 x 2.5" Slim HD Space for enough Storage Device requirement.

### Technical Data:

Dimension	50 H x 275 W x 172 D mm
Material	Aluminum
Color	Black
Weight	2 Kgs ( Include M/B )
Storage Space	2.5" HD x 1

### Order information:

M/B Model	Description
CV860A	All-in One M/B
CV860C	4 Com Ports M/B
CV863A	2 PCMCIA Slot / 4 Lan Ports M/B
CV866C	4 Com Ports M/B / LCD LVDS Interface Support M/B
SV823A	4-16 Video in by BNC Connector M/B
MV823A	2 IEEE1394 / Video in & out support M/B
MV823S	Video out support M/B

### Option ( Please Ref. M/B Spec )

Wireless Lan	Chip: ATMEL , USB Interface , 802.11b Standard , Driver :Win98,ME,2K,XP,Linux, 128bit WEP Encryption Support
56K Modem(ST)	Chip: ST , USB Interface , Driver: Win98,ME,2K,XP,Linux
56K Modem(CX)	Chip: Conexant , USB Interface , Driver: Win98,ME,2K,XP.
ISDN	Chip: Cologne, ISDN Standard ETSI Euro ISDN, Driver: Win98,ME,2K,XP,Linux
ADSL	Chip: Conexant , ANSI T1.413 Issue 2, ITU-T G.992( G.dmt ) and G.992.2(G.lite) Annex A,B. Driver: Win98,ME,2K,XP,Linux

