

12.1"



● Specification

| | |
|--------------------------------|--------------------------------|
| Model Name | R12T600-CHL1 |
| Viewable Size Image | 12.1" |
| Active Display Area(mm) | 245.76(H)x184.32(V) |
| Pixel Pitch(mm) | 0.3075(H)x0.3075(V)(typ.) |
| Number of Pixels | 800x600 |
| Contrast Ratio | 200:1(typ.) |
| Display Color | 262,144(6bit/colors) |
| Brightness(CD/m ²) | 300 |
| Viewing Angel(CR>=10) | -60~60(H);-55~40(V) |
| Synchronization Range | |
| Horizontal/Vertical | 31.5~68KHz/56~75Hz |
| Recommended Resolution | 800x600@60Hz, 75Hz |
| Signal Connector | 15pin D-sub |
| Power Source | AC100~240V, Universal, ±10% |
| Power Consumption | 33W typical, normal operation |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Optional Video Input | S-Video, Composite |
| Optional DVI Input | No |
| Optional Touch Screen | Resistive, Capacitive, SAW, IR |

Remarks: R12T600 series=VGA input only
 R12T630 series=VGA+Video input